

04-19-00

A

04/18/00



ASSISTANT COMMISSIONER OF PATENTS AND TRADEMARKS  
Washington, DC 20231

PATENT  
Date: April 18, 2000  
File No. 1324.63957

Sir:

Transmitted herewith for filing is the patent application of

Inventor(s): Yoshio Nagahiro

I hereby certify that this paper is being deposited with the United States Postal Service as Express Mail in an envelope addressed to: Asst. Comm. for Patents, Washington, D.C. 20231, on this date.

For: ACTIVE MATRIX TYPE DISPLAY

04-18-00  
Date

Express Mail Label No.: EL409492161US

Enclosed are:

- (X) 26 pages of specification, including 9 claims and an abstract.  
(X) an executed oath or declaration, with power of attorney.  
( ) an unexecuted oath or declaration, with power of attorney.  
( )        sheet(s) of informal drawing(s).  
(X) 7 sheet(s) of formal drawings(s).  
(X) Assignment(s) of the invention to FUJITSU LIMITED.  
(X) Assignment Form Cover Sheet.  
(X) A check in the amount of \$ 40.00 to cover the fee for recording the assignment(s) is enclosed.  
( ) Information Disclosure Statement.  
( ) Form PTO-1449 and cited references.  
( ) Associate power of attorney.  
(X) Priority Document.

jc564 U.S. PTO  
09/551362



Fee Calculation For Claims As Filed

a) Basic Fee						\$ 690.00
b) Independent Claims	<u>1</u>	- 3 =	<u>0</u>	x \$ 78.00 =	\$	
c) Total Claims	<u>9</u>	- 20 =	<u>0</u>	x \$ 18.00 =	\$	
d) Fee for Multiple Claims				\$260.00 =	\$	
Total Filing Fee					\$	<u>690.00</u>

- ( )        Statement(s) of Status as Small Entity, reducing Filing Fee by half to \$         
(X) A check in the amount of \$ 690.00 to cover the filing fee is enclosed.  
(X) The Commissioner is hereby authorized to charge any additional fees which may be required to this application under 37 C.F.R. §§1.16-1.17, or credit any overpayment, to Deposit Account No. 07-2069. Should no proper payment be enclosed herewith, as by a check being in the wrong amount, unsigned, post-dated, otherwise improper or informal or even entirely missing, the Commissioner is authorized to charge the unpaid amount to Deposit Account No. 07-2069. A duplicate copy of this sheet is enclosed.

April 18, 2000  
Suite 8660 - Sears Tower  
233 S. Wacker Drive  
Chicago, Illinois 60606  
(312) 993-0080

GREER, BURNS &amp; CRAIN, LTD.

By:   
Patrick G. Burns  
Registration No. 29,367

04-18-00

Date

Express Mail Label No.:  
EL409492161US

## ACTIVE MATRIX TYPE DISPLAY

BACKGROUND OF THE INVENTION:

## 1. Field of the Invention

The present invention relates to an active matrix type display provided with a thin film transistor (hereinafter, referred to as a TFT) as a switching device and more particularly to liquid crystal display (hereinafter, referred to as a LCD) which displays an image by driving liquid crystal according to the TFT.

## 2. Description of the Related Art

A thin film transistor array using amorphous silicon or polycrystal silicon (polysilicon) as an operational semiconductor film is used as a switching device for an active matrix type liquid crystal display panel and the like.

Fig. 6 shows a schematic structure of an array substrate for the conventional liquid crystal display panel using the TFT. Fig. 6(a) shows a plan view of the array substrate and Fig. 6(b) shows a part of a cross section cut at a line A-A in Fig. 6(a). As shown in Fig. 6(a), a plurality of gate wirings 4 are formed on a glass substrate 1. Further, a plurality of data wirings 6 are formed in the orthogonal direction to the gate wirings 4. The TFT is formed in a pixel area decided by the gate wirings 4 and the data wirings 6. According to a structure of the TFT shown in Fig. 6, a gate electrode is not formed by being pulled out of the gate wiring 4, and the TFT is structured to use a part of the gate wiring 4 wired lineally as the gate electrode. Furthermore, this TFT has the

so-called double gate structure in which the gate wiring 4 is crossed twice.

In the pixel area, a pixel electrode 7 to be connected to the TFT is formed. Further, a storage capacitor wiring 41 is formed by crossing the pixel area in parallel with the gate wirings 4 and furthermore, a storage capacitor electrode 62 to be electrically connected to the storage capacitor wiring 41 at each pixel area is formed.

Furthermore, as shown in Fig. 6(b), a semiconductor layer 2 made of polysilicon is formed on the glass substrate 1, and a gate insulating film 3 made of silicon oxide film ( $\text{SiO}_2$ ) and a gate electrode (gate wiring) 4 made of chrome (Cr) are formed in this order on the semiconductor layer 2. The semiconductor layer 2 has a channel layer 2a, a source electrode 2c and a drain electrode 2b which are semiconductor layers to which impurity is doped. A first interlayer insulating film 51 is formed substantially on the whole surface of the upper layer of the gate electrode 4, and a drain electrode 2f is connected to the data wiring 6 via a contact hole 51a (refer to Fig. 6(a)). A source electrode 2e is arranged opposing to the drain electrode 2f sandwiching a channel layer 2g. The source electrode 2e functions as the drain electrode 2b in a transistor at next stage. The source electrode 2c is arranged opposing to the drain electrode 2b while sandwiching the channel layer 2a. Also, the source electrode 2c and an island-like electrode 61 are connected via a contact hole 51b. The island-like electrode 61 is formed simultaneously with a formation of the data wiring 6 made of, for example, Mo (Molybdenum). The island-like electrode 61 is connected to the pixel electrode 7 made of a transparent electrode such as ITO

(Indium Tin Oxide) via a contact hole 52c in a second interlayer insulating film 52 formed above the island-like electrode 61.

On the other hand, simultaneously with the formation of the gate electrode 4, the storage capacitor wiring 41 is formed in parallel with the gate electrode 4. A storage capacitor electrode 62 is formed on the storage capacitor wiring 41 via a contact hole 51d in the first interlayer insulating film 51. The storage capacitor electrode 62 is formed simultaneously with the formation of the data wiring 6. The storage capacitor electrode 62 forms a storage capacitor Cs between the pixel electrode 7 and the storage capacitor electrode 62 sandwiching the second interlayer insulating film 52. It will be noted that, in order to maintain a constant potential, for example, the storage capacitor wiring 41 is electrically connected to a common electrode formed on the opposing substrate side arranged to face the glass substrate 1. Liquid crystal is sealed between the array substrate where the pixel is formed on the glass substrate and the opposing substrate. When the TFT writes electric charges in a liquid crystal capacitor via the pixel electrode 7 to display an image, the TFT simultaneously writes the electric charges in the storage capacitor. In general, the capacitance which is substantially from the same as the capacitance of liquid crystal to several times as much as the capacitance of liquid crystal is required for the storage capacitor.

Fig. 7 shows other structure of the array substrate for the conventional liquid crystal display panel using the TFT. Fig. 7(a) shows a plan view of the array substrate and Fig. 7(b) shows a part of a cross section cut at a line B-B in Fig. 7(a). As shown in Fig. 7(a), a plurality of gate wirings 4 are formed on the glass substrate

1. Further, a plurality of data wirings 6 are formed in the orthogonal direction to the gate wirings 4. The TFT is formed in the pixel area decided by the gate wirings 4 and the data wirings 6. According to the structure of the TFT shown in Fig. 7, a gate electrode is not formed by being pulled out of the gate wiring 4, and the structure of the TFT is structured to use a part of the gate wiring 4 wired lineally as the gate electrode. Furthermore, this TFT has the so-called double gate structure in which the gate wiring 4 is crossed twice.

In the pixel area, the pixel electrode 7 to be connected to the TFT is formed. Further, a storage capacitor electrode 8 is formed surrounding the circumference of the pixel electrode 7. This storage capacitor electrode 8 also serves as a black matrix layer (black matrix) normally formed on the opposing substrate side facing the array substrate where the TFT is formed sandwiching a liquid crystal layer.

Furthermore, as shown in Fig. 7(b), the semiconductor layer 2 made of polysilicon is formed on the glass substrate 1, and the gate insulating film 3 made of silicon oxide film and the gate electrode (gate wiring) 4 made of Cr are formed on the semiconductor layer 2. The semiconductor layer 2 has a channel layer 2a, and a source electrode 2c and a drain electrode 2b which are semiconductor layers to which impurity is doped. The first interlayer insulating film 5i is formed substantially on the whole surface of the upper layer of the gate electrode 4, and a drain electrode 2f is connected to the data wiring 6 via a contact hole 5la (refer to Fig. 7(a)). A source electrode 2e is arranged opposing to the drain electrode 2f sandwiching a channel layer 2g. The source electrode 2e functions

as a drain electrode 2b in a transistor at next stage. The source electrode 2c is arranged opposing to the drain electrode 2b sandwiching the channel layer 2a. Also, the source electrode 2c and the island-like electrode 61 are connected via the contact hole 51b. The island-like electrode 61 is made of, for example, Mo and formed simultaneously with the formation of the data wiring 6. The island-like electrode 61 is connected to the pixel electrode 7 made of a transparent electrode such as ITO via a contact hole 53c opened in the second interlayer insulating film 52 and a third interlayer insulating film 53 formed above the island-like electrode 61.

The storage capacitor electrode 8 made of, for example, titanium is formed between the second interlayer insulating film 52 and the third interlayer insulating film 53. The storage capacitor electrode 8 which also serves as the black matrix layer forms a storage capacitor Cs between the pixel electrode 7 and the storage capacitor electrode 8 sandwiching the third interlayer insulating film 53. Further, the storage capacitor electrode 8 is connected to, for example, the common electrode in order to maintain the constant potential.

In order to increase storage capacity in the display described above, methods such as increasing a relative dielectric constant of an insulating film between electrodes, decreasing the thickness of the insulating film, or increasing the area of a storage capacitor electrode are generally considered. However, there is problems that in the method of increasing the relative dielectric constant of the insulating film, a material for the insulating film is limited, and in the method of decreasing the thickness of the insulating film, an occurrence of an interlayer short-circuit between electrodes is

concerned.

Further, though the display is desired to display as high as possible in brightness, in the method of increasing an electrode area, the area of the storage capacitor electrode formed by a metal material which does not pass the light extends inside the pixel electrode 7 and much of transmitting light from the back lighting is shielded at the storage capacitor electrode. Therefore, when obtaining a bright display panel with high aperture ratio by increasing the area on which the back lighting light is incident, a problem exists where the storage capacitor can not be increased.

SUMMARY OF THE INVENTION:

An object of the present invention is to provide an active matrix type display from which a large storage capacity can be obtained without thinning an insulating layer between electrodes nor expanding the electrode to a pixel area.

Above object is achieved by an active matrix type display comprising a plurality of gate wirings formed on a substrate, a plurality of data wirings formed on the substrate substantially orthogonal to the gate wirings, a thin film transistor formed in a plurality of pixel areas decided by the gate wirings and the data wirings and arranged in a matrix shape, a pixel electrode formed in the pixel area and connected to the thin film transistor, and a plurality of storage capacitor electrodes forming a plurality of storage capacitors between the substrate, the pixel electrode and the storage capacitor electrodes via a plurality of insulating films.

According to the present invention, by laminating storage capacitors to structure a plurality of layers, capacity can be increased without generating an increase of a shielding area which reduces the aperture ratio of the pixel.

Further, in addition to the conventional storage capacitor, by laminating storage capacitors to a plurality of layered structures in the area where a conventional storage capacitor electrode originally shields a light, storage capacity can be increased without reducing the aperture ratio of the pixel. It will be noted that, the active matrix type display according to the present invention uses the same device forming materials as in the conventional display and can be fabricated by the same fabrication method as before.

#### BRIEF DESCRIPTION OF THE DRAWINGS:

The present invention is further described in connection with the accompanying drawings, in which:

Fig. 1 is a diagram showing a structure of an active matrix type display according to a first embodiment of the present invention.

Fig. 2 is a diagram showing a fabrication method of the active matrix type display according to the first embodiment of the present invention.

Fig. 3 is a diagram showing another structure of an active matrix type display according to the first embodiment of the present invention.

Fig. 4 is a diagram showing a structure of an active matrix



type display according to a second embodiment of the present invention.

Fig. 5 is a diagram showing a fabrication method of the active matrix type display according to the second embodiment of the present invention.

Fig. 6 is a diagram showing a structure of the conventional active matrix type display.

Fig. 7 is a diagram showing other structure of the conventional active matrix type display.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS:

An active matrix type display according to a first embodiment of the present invention is described with reference to Fig. 1 through Fig. 3. First, a schematic structure of the active matrix type display according to this embodiment is described with reference to Fig. 1. Fig. 1(a) shows a plan view of an array substrate and Fig. 1(b) shows a part of a cross section cut at a line A-A in Fig. 1(a). As shown in Fig. 1(a), on a substrate made of transparent glass, which is to be the array substrate, a plurality of gate wirings 4 extending in the lateral direction in the diagram are formed in line in parallel. Further, a plurality of data wirings 6 are formed in line in parallel substantially in the orthogonal direction to the gate wirings 4.

A rectangular-shape area decided by each gate wiring 4 and each data wiring 6 becomes a pixel area and a plurality of the pixel areas are arranged in a matrix shape. In each pixel area, TFT is formed. According to a structure of the TFT shown in Fig. 1, a gate

electrode is not formed by being pulled out of the gate wiring 4, the TFT is structured to use a part of the gate wiring 4 wired lineally as the gate electrode. Further, in order to make a reduction in leak current, this TFT has the so-called double gate structure in which the gate wiring 4 is crossed twice. Thus, a drain electrode 2f is connected with the data wiring 6 at a contact hole 51a. A source electrode 2e is arranged opposing to the drain electrode 2f sandwiching a channel layer 2g. The source electrode 2e functions as a drain electrode 2b in a transistor at next stage. A source electrode 2c is arranged opposing to the drain electrode 2b sandwiching a channel layer 2a.

In the pixel area, a pixel electrode 7 which has substantially the same outward shape as an outline of the pixel area is formed. The pixel electrode 7 is connected with the source electrode 2c of the TFT at the contact holes 51b and 52c. Further, a storage capacitor wiring 41 which crosses inside the pixel area in parallel with the gate wiring 4 is formed. Furthermore, for example, a rectangular-shape storage capacitor electrode (hereinafter, referred to as a second storage capacitor electrode) 62 which is electrically connected to the storage capacitor wiring 41 via a contact hole 51d at each pixel area is formed. Also, in this embodiment, an impurity semiconductor layer composing the source electrode 2c is formed extending to the lower part of the second storage capacitor electrode 62. Further, the impurity semiconductor layer is formed at the lower part of the second storage capacitor electrode 62 along the storage capacitor wiring 41, thereby functioning as a first storage capacitor electrode 2d.

Description in more detail follows with reference to a device

cross section shown in Fig. 1(b). A semiconductor layer 2 made of, for example, polysilicon is formed on the transparent glass substrate 1 and a gate insulating film 3 made of, for example, a silicon oxide film and the gate electrode (gate wiring) 4 made of, for example, Cr are formed on the semiconductor layer 2. The semiconductor layer 2 functions as channel layers 2a and 2g, source electrodes 2c and 2e which are impurity semiconductor layers and drain electrodes 2b and 2f. Further, a first interlayer insulating film 51 is formed on the first storage capacitor electrode 2d which extends to the lower part of the second storage capacitor electrode 62. The source electrode 2c is connected to an island-like electrode 61 simultaneously formed with the formation of the data wiring 6 via the contact hole 51b. The island-like electrode 61 is made of the same material composing the data wiring 6, for example, Mo. The island-like electrode 61 is connected to the pixel electrode 7 made of a transparent electrode such as ITO via the contact hole 52c at the second interlayer insulating film 52 formed thereabove.

In this manner, the TFT according to this embodiment has the channel layer (an operating semiconductor layer) 2a formed on the glass substrate 1, the gate insulating film 3 formed on the operating semiconductor layer 2a, the gate electrode 4 to be connected to the gate wiring 4 formed on the gate insulating film 3, the source electrode (the first semiconductor layer) 2c including impurity formed at both sides of the operating semiconductor layer 2a, and the drain electrode (a second semiconductor layer) 2b. The source electrode 2c is electrically connected to the pixel electrode 7 via the contact hole 51b opened in the first interlayer insulating film 51 and the contact hole 52c opened in the second interlayer

insulating film 52 formed thereabove. The drain electrode 2f is connected to the data wiring 6 via the contact hole 51a. Therefore, the TFT has a planer-type structure.

On the other hand, the storage capacitor wiring 41 is formed in parallel with the gate electrode 4 simultaneously with the formation of the gate electrode 4. The second storage capacitor electrode 62 is formed on the storage capacitor wiring 41 via the contact hole 51d at the first interlayer insulating film 51. The second storage capacitor electrode 62 is simultaneously formed when the data wiring 6 is formed. The storage capacitor electrode 62 forms a storage capacitor Cs2 between the pixel electrode 7 and the storage capacitor electrode 62 sandwiching the second interlayer insulating film 52. Further, the second storage capacitor electrode 62 forms a storage capacitor Cs1 between the first storage capacitor electrode 2d and the second storage capacitor electrode 62 sandwiching the first interlayer insulating film 51. It will be noted that, in order to maintain a predetermined potential, the storage capacitor wiring 41, for example, is electrically connected to a common electrode formed on an opposing substrate arranged to face the glass substrate 1 and is maintained at a common potential. Liquid crystal (not shown) is sealed between the array substrate in which the pixel is formed on the glass substrate 1 and the opposing substrate (not shown). When the TFT writes electric charges to display an image in a liquid crystal capacitor via the pixel electrode 7, the electric charge are simultaneously written in the storage capacitor.

Since the first storage capacitor electrode 2d and the pixel electrode 7 are connected via the contact holes 51b and 52c, the

storage capacitors Cs1 and Cs2 are connected in parallel. Thus, a whole storage capacitance is equal to Cs1 + Cs2.

In this manner, a distinctive feature is that this embodiment has a plurality of gate wirings 4 formed on the glass substrate 1, a plurality of data wirings 6 formed on the glass substrate 1 substantially in the orthogonal direction to the gate wirings 4, the TFT formed in a plurality of pixel areas which are decided by the gate wiring 4 and the data wiring 6 and arranged in a matrix pattern, the pixel electrode 7 formed in the pixel area and connected to the TFT, and a plurality of the storage capacitor electrode layers (2d, 62) forming a plurality of storage capacitors Cs1 and Cs2 via a plurality of insulating films (51, 52) between the glass substrate 1 and the pixel electrode 7. Also, a distinctive feature is that a plurality of storage capacitors Cs1 and Cs2 are connected in parallel.

Further, a plurality of the storage capacitor electrodes 2d and 62 are laminated to overlap via the first interlayer insulating film when observing from a direction perpendicular to the substrate. In other words, a plurality of the storage capacitor electrodes 2d and 62 use the area where the first semiconductor layer is extended as the first storage capacitor electrode 2d and have the second storage capacitor electrode 62 which is formed between the first interlayer insulating film 51 and the second interlayer insulating film 52 and connected to the storage capacitor wiring 41 which is maintained at a predetermined potential. At least the first storage capacitor Cs1 is composed of the first storage capacitor electrode 2d, the first interlayer insulating film 51 and the second storage capacitor electrode layer 62 while the second storage capacitor Cs2

is composed of the second storage capacitor electrode 62, the second interlayer insulating film 52 and the pixel electrode 7. In this manner, by laminating the storage capacitor to a two-layer structure of Cs1 and Cs2, the capacitance can be increased without producing an increase in a shielding area which reduces an aperture ratio of the pixel.

Next, a fabrication method of the active matrix type display according to this embodiment is described with reference to Fig. 2. Fig. 2 is a cross sectional view showing a process to form the same area as the cross section shown in Fig. 1(b).

First, as shown in Fig. 2(a), the semiconductor layer 2 made of, for example, polysilicon is formed to approximately 40 nm in thickness. This semiconductor layer 2 is formed to an area where the source electrode 2c side is extended and becomes the first storage capacitor electrode 2d in later processes. Next, for example, SiO<sub>2</sub> is deposited to approximately 100 nm in thickness on a whole surface and then, for example, Cr is deposited to 200 nm in thickness and patterned, thereby forming the gate insulating film 3 and an insulating film 3' as well as the gate electrode 4 on the gate insulating film 3 and the storage capacitor wiring 41 on the insulating film 3'.

Next, as shown in Fig. 2(b), implantation of impurity is performed by using the gate electrode 4 as a mask, thereby forming the source electrode 2c and the drain electrode 2b by a self-alignment. At this time, the first storage capacitor electrode 2d is formed at the impurity semiconductor layer extending to the source electrode 2c side. Then, the first interlayer insulating film 51 is formed by depositing, for example, silicon nitride film (SiN)

to, for example, 300 nm in thickness. After that, the contact holes 51b and 51d are opened in the first interlayer insulating film 51 on the source electrode 2c and the storage capacitor wiring 41.

Next, as shown in Fig. 2(c), the data wiring 6 is formed by depositing a Ti film to approximately 30 nm in thickness and a Mo film to approximately 300 nm in this order and patterning them. Simultaneously with the formation of this data wiring 6, the island-like electrode 61 is formed at the contact hole 51b for contacting the ITO of the pixel electrode 7 and the source electrode 2c of the TFT. Similarly, the second storage capacitor electrode 62 connected to the storage capacitor wiring 41 via the contact hole 51d is formed.

Next, as shown in Fig. 2(d), the second interlayer insulating film 52 is formed by depositing a SiN film to approximately 300 nm in thickness. Then, the contact hole 52c is opened in the second interlayer insulating film 52 on the island-like electrode 61. After that, the pixel electrode 7 is formed by forming the ITO to approximately 100 nm in thickness and patterning.

By the aforementioned process, a device forming process on the array substrate side of the active matrix type display is completed. Thus, the second storage capacitor Cs2 is formed by the second storage capacitor electrode 62 and the pixel electrode 7 sandwiching the second interlayer insulating film 52, and the first storage capacitor Cs1 is formed by the second storage capacitor electrode 62 and the first storage capacitor electrode 2d sandwiching the first interlayer insulating film 51. As evident from the aforementioned description, the active matrix type display according to this embodiment can be fabricated by using the same device forming

materials as in the conventional display and by the same fabrication method as before.

At the end, liquid crystal is filled by laminating the array substrate with the opposing substrate, the liquid crystal is sealed with a predetermined cell gap, a driver IC and the like for driving the liquid crystal is built in and if necessary a back lighting is attached to complete the active matrix type display.

Next, an example of a variation of an active matrix type liquid crystal display according to this embodiment is described with reference to Fig.3. In a structure shown in Fig.3, the same code is referred to the same structure element as that shown in Fig.1 and Fig. 2 and the description is omitted.

When taking a long distance between the gate wiring 4 and the storage capacitor wiring 41 in the structure shown in Fig.1, it is required to form a first storage capacitor electrode 2d by extending the impurity semiconductor layer from the island-like electrode 61 to the storage capacitor wiring 41. However, since the semiconductor layer shades the light to some extent, drawing around too long distance in the pixel area results in a reduction in aperture ratio of the pixel.

So, in the structure shown in Fig. 3, the first storage capacitor electrode 2d is separately formed isolated from the source electrode 2c (the first semiconductor layer). Therefore, the first storage capacitor electrode 2d is electrically connected to an island-like electrode 65 via another contact hole 51j formed on the first interlayer insulating film 51. Thus, the island-like electrode 65 is connected to the pixel electrode 7 via a contact hole 52k formed on the second interlayer insulating film 52. It will be



noted that an island-line electrode 65 is simultaneously formed when the island-electrode 61 is formed.

According to this structure, the storage capacitance can be increased without a reduction in aperture ratio of the pixel.

Next, the active matrix type display according to a second embodiment of the present invention is described with reference to Fig. 4 and Fig. 5. First, a schematic structure of the active matrix type display according to this embodiment is described with reference to Fig. 4. Fig. 4(a) shows a plan view of the array substrate and the Fig. 4(b), which is a part of a cross section cut by a line B-B in Fig. 4(a), shows a cross section of the gate wiring 4 area. As shown in Fig. 4(a), on the transparent glass substrate 1, which is to be the array substrate, a plurality of gate wirings 4 (4a, 4b only shown) extending in the lateral direction in the diagram are formed in line in parallel. Further, substantially in the orthogonal direction to the gate wirings 4, a plurality of data wirings 6 are formed in line in parallel. A rectangular-shape area decided by each gate wiring 4 and each data wiring 6 becomes the pixel area and a plurality of pixel areas are arranged in a matrix shape. The TFT is formed in each pixel area. The TFT structure shown in Fig. 4 is the same as the one described with reference to Fig. 1 in the first embodiment and uses a part of the gate wiring 4 wired lineally as the gate electrode. Further, the TFT structure has the so-called double gate structure in which the gate wiring 4 is crossed twice.

In the pixel area, the pixel electrode 7 which has substantially the same outward shape as the outline of the pixel area is formed. The pixel electrode 7 is connected to the source electrode

2c of the TFT at the contact holes 51b and 52c.

In this embodiment, unlike the first embodiment, the impurity semiconductor layer composing the source electrode 2c does not extend and the first storage capacitor electrode 2d is not formed. Instead, a fourth storage capacitor electrode 8 which also serves as a storage capacitor wiring is formed. The fourth storage capacitor electrode 8 has a peripheral area overlapping a perimeter area of the pixel electrode 7 via a third interlayer insulating film 53 when observing from a direction perpendicular to the substrate. Further, the fourth storage capacitor electrode 8 also serves as a black matrix layer normally formed on the opposing substrate side which faces the array substrate, on which the TFT is formed, sandwiching the liquid crystal layer. The black matrix layer is so as not to leak back lighting light from an area where the pixel electrode 7 is not formed. In a high fine display panel and the like having a small area for one pixel, forming the black matrix layer on the array substrate side is particularly effective in preventing a transmitting light out of the back lighting from reducing due to an error in laminating panel alignment between the opposing substrate and the array substrate. Furthermore, a third storage capacitor electrode 62 is formed below the fourth storage capacitor electrode 8 via an insulating film.

Here, further description follows with reference to Fig. 4(a) as well as Fig. 4(b). The third storage capacitor electrode 62 according to this embodiment is formed on the first interlayer insulating film 51 formed above the gate wiring 4. The second interlayer insulating film 52 is formed on the third storage capacitor electrode 62 and the fourth storage capacitor electrode

8 is placed above the second interlayer insulating film 52. The third interlayer insulating film 53 is formed on the fourth storage capacitor electrode 8. The pixel electrode 7 made of ITO and the like is formed on the third interlayer insulating film 53 in each pixel area.

As shown in Fig. 4(a), a part of the third storage capacitor electrode 62 on the gate wiring 4b is pulled out and connected to the pixel electrode 7 via a contact hole 53e in which the pixel electrode 7 is connected to the TFT driven by a gate signal running to the gate next wiring 4a.

In such a structure, a third storage capacitor Cs3 is composed of the third storage capacitor electrode 62, the second interlayer insulating film 52, and the fourth storage capacitor electrode 8. A fourth storage capacitor Cs4 is composed of the fourth storage capacitor electrode 8, the third interlayer insulating film 53, and the pixel electrode 7. Further, a fifth storage capacitor Cs5 is composed of the third storage capacitor electrode 62, the first interlayer insulating film 51, and the gate wiring 4 (4b). It will be noted that the fourth storage capacitor electrode 8 is maintained at the common potential by, for example, being connected to the common electrode in order to keep the predetermined potential.

In the aforementioned structure, since the third storage capacitor electrode 62 and the pixel electrode 7 are electrically connected via the contact hole 53e, the third storage capacitor Cs3 and the fourth storage capacitor Cs4 are connected in parallel. Further, though one side of the electrode forming the fifth storage capacitor Cs5 is an adjacent gate electrode 4b, its gate potential varies only during an extremely short period when the gate signal

is written, and is at the predetermined potential at most of other time. During this period when the potential is constant, one side of the fifth storage capacitor Cs5 is used as the storage capacitor electrode. Therefore, since the third through fifth storage capacitors Cs3 through Cs5 can be regarded as being connected in parallel, whole storage capacitance is substantially equal to  $Cs3 + Cs4 + Cs5$ . Further, since the third storage capacitor electrode 62 is positioned to be hidden behind the fourth storage capacitor electrode 8 against the back lighting light, the third storage capacitor electrode 62, excluding a part contacted with the pixel electrode 7, does not prevent the transmitting light in the pixel area.

As described above, according to this embodiment, in addition to the fourth storage capacitor Cs4 which is also formed in the conventional structure, by creating a three-layer structure laminating the third and the fifth storage capacitors Cs3 and Cs5 in the area where light is shielded by fourth storage capacitor electrode 8, the light shielding area at the contact hole 53e at the third storage capacitor electrode 62 and the pixel electrode 7 can only be slightly increased, thereby largely increasing the storage capacity.

Next, a fabrication method of the active matrix type display according to this embodiment is described with reference to Fig. 5. Fig. 5 is a cross sectional view showing a process to form the same area as the cross section shown in Fig. 4(b).

First, on the glass substrate 1 which is a transparent insulating substrate, the semiconductor layer 2 made of, for example, polysilicon is formed to approximately 40 nm in thickness and

patterned. Then, as shown in Fig. 5(a), for example,  $\text{SiO}_2$  is deposited to approximately 100 nm in thickness on a whole surface. Next, by depositing, for example, Cr to 200 nm in thickness and patterning, the gate insulating film 3 and the gate electrode 4 are formed.

Next, implantation of the impurity is performed by using the gate electrode 4 as a mask and the source electrode 2c and the drain electrode 2b of the TFT are formed by self-alignment (not shown). Then, the first interlayer insulating film 51 is formed by depositing, for example, a silicon nitride film ( $\text{SiN}$ ) to, for example, 300 nm in thickness.

Next, the data wiring 6 is formed by depositing the Ti film to approximately 30 nm in thickness and the Mo film to approximately 300 nm in thickness in this order and patterning them (not shown). Simultaneously with the formation of this data wiring 6, the island-like electrode 61 and the like for contacting the pixel electrode 7 with the source electrode 2c of the TFT is also formed (not shown). In the same way, the third storage capacitor electrode 62 is formed on the gate wiring 4 via the first interlayer insulating film 51.

Next, as shown in Fig. 5(b), the second interlayer insulating film 52 is formed by depositing a  $\text{SiN}$  film to approximately 400 nm in thickness. Then, the fourth storage capacitor electrode 8 also serving as the black matrix layer is formed by depositing a Ti film to, for example, 200 nm in thickness on the second interlayer insulating film 52 and patterning.

Then, as shown in Fig. 5(c), the third interlayer insulating film 53 made of a  $\text{SiN}$  film of, for example, 400 nm in thickness is

formed and the contact hole 53e is opened on the third storage capacitor electrode 62 by passing through the third and the second interlayer insulating films 53 and 52. Further, the pixel electrode 7 is formed by forming the ITO to, for example, 100 nm in thickness and patterning.

By the aforementioned processes, a device forming process on the array substrate side of the active matrix type display is completed. By this completion, the third storage capacitor Cs3 is formed by the third storage capacitor electrode 62, the second interlayer insulating film 52 and the fourth storage capacitor electrode 8, and the fourth storage capacitor Cs4 is formed by the fourth storage capacitor electrode 8, the third interlayer insulating film 53 and the pixel electrode 7. Further, the fifth storage capacitor Cs5 is formed by the third storage capacitor electrode 62, the first interlayer insulating film 51 and the gate wiring 4 (4b). As evident from the aforementioned description, the active matrix type display according to this embodiment can be fabricated by using the same device forming materials as in the conventional display and by the same fabrication method as before.

At the end, the liquid crystal is filled by laminating the array substrate with the opposing substrate, the liquid crystal is sealed with the predetermined cell gap, a driver IC and the like for driving the liquid crystal is built in, and if necessary the back lighting is attached to complete the active matrix type display.

The present invention is not limited to the above embodiment and various variations are possible. For example, though the planer-type TFT is used to describe in the above embodiment, the present invention can be applied to the TFT having a staggered or

an inverted staggered structure.

Furthermore, though the second embodiment above is described by using the structure in which the fourth storage capacitor electrode 8 also serves as the storage capacitor wiring, the present invention is not limited to this and the structure can certainly be structured so that the fourth storage capacitor electrode 8 and the storage capacitor wiring are separately established and are electrically connected.

As described above, according to the present invention, capacitance can be increased by laminating storage capacitors without increasing the area for the storage capacitors toward a display area. Therefore, a bright display having a sufficient storage capacitance and a large area as well which transmits the back lighting light can be provided. By having the sufficient storage capacitance, variations of the optimum common potential due to the capacitance between the gate and the pixel can be suppressed and dot defects due to off-leak current of the TFT can also be prevented. Further, the array substrate for the TFT according to the present invention can be fabricated by the same fabrication method using the same device forming materials as before.

## [CLAIMS]

What is claimed is:

1. An active matrix type display comprising:
  - a plurality of gate wirings formed on a substrate;
  - a plurality of data wirings formed on the substrate substantially orthogonal to the gate wirings;
  - a thin film transistor formed in a plurality of pixel areas decided by the gate wirings and the data wirings and arranged in a matrix shape;
  - a pixel electrode formed in the pixel area and connected to the thin film transistor; and
  - a plurality of storage capacitor electrodes forming a plurality of storage capacitors between the substrate, the pixel electrode and the storage capacitor electrodes via a plurality of insulating films.
2. An active matrix type display as set forth in claim 1, wherein a plurality of the storage capacitors are connected in parallel.
3. An active matrix type display as set forth in claim 1, wherein at least more than two layers among a plurality of the storage capacitor electrodes are laminated to overlap via a insulating film viewing from the direction perpendicular to the substrate.
4. An active matrix type display as set forth in claim 1, wherein the thin film transistor is a planer type structure having an operating semiconductor layer formed on the substrate, a gate



insulating film formed on the operating semiconductor layer, a gate electrode formed on the gate insulating film, a first and second semiconductor layers formed on both sides of the operating semiconductor layer including impurity, a source electrode including the first semiconductor layer electrically connected to the pixel electrode via a contact window opened to the first and second insulating layers laminated on the first semiconductor layer, and a drain electrode including the second semiconductor layer and connected to the data wirings;

the gate wirings also serving as the gate electrode; and  
a plurality of the storage capacitor electrodes using the first semiconductor layer as a first storage capacitor electrode, having a second storage capacitor electrode being formed between the first insulating film and the second insulating film and connected to a storage capacitor wiring maintained at a predetermined potential, wherein at least a first storage capacitor is structured by the first storage capacitor electrode, the first insulating film and the second storage capacitor electrode, and a second storage capacitor is structured by the second storage capacitor electrode, the second insulating film and the pixel electrode.

5. An active matrix type display as set forth in claim 4, wherein the first storage capacitor electrode uses a semiconductor layer formed isolated from the first semiconductor layer instead of the first semiconductor layer.

6. An active matrix type display as set forth in claim 1, wherein a plurality of the storage capacitor electrodes have a third storage

capacitor electrode formed on the first insulating film in the gate wiring area at a previous stage of the pixel area and connected to the pixel electrode in the pixel area, and a fourth storage capacitor electrode formed on the second insulating film in the gate wiring area and the data wiring area and providing an end of the pixel electrode formed on a third insulating film formed at upper portion and an end overlapping viewing the substrate perpendicularly, wherein a third storage capacitor is structured by the third storage capacitor electrode, the second insulating film and the fourth storage capacitor electrode, and the fourth storage capacitor is structured by the fourth storage capacity electrode, the third insulating film and the pixel electrode.

7. An active matrix type display as set forth in claim 6, wherein a fifth storage capacitor is structured by the third storage capacitor electrode, the first insulating film and the gate wiring.

8. An active matrix type display as set forth in claim 6, wherein the fourth storage capacitor electrode also serves as a storage capacitor wiring.

9. An active matrix type display as set forth in claim 6, the fourth storage capacitor electrode also serves as a shading film.

ABSTRACT

The present invention relates to an active matrix type display providing a thin film transistor (TFT) as a switching device and the object is to provide an active matrix type display which can obtain large storage capacitor without thinning an insulating film between electrodes nor expanding an electrode to a pixel area. The active matrix type display is structured to have a plurality of gate wirings 4 formed on a glass substrate 1, a plurality of data wirings 6 formed on the glass substrate 1 substantially orthogonally to the gate wirings 4, the TFT decided by the gate wirings 4 and data wirings 6 and formed in a plurality of pixel areas arranged in a matrix shape, a pixel electrode 7 formed inside the pixel area and connected to the TFT, and a plurality of storage capacitor electrodes layers (2d, 62) forming a plurality of storage capacitors Cs1 and Cs2 between the glass substrate 1 and pixel electrode 7 via a plurality of insulating films (51,52).

FIG. 1






FIG. 2


(a)



(b)



(c)



(d)




FIG. 3






FIG. 4



(b)






FIG. 5


(a)



(b)



(c)










FIG. 7



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## Declaration and Power of Attorney For Patent Application

### 特許出願宣言書及び委任状

### Japanese Language Declaration

### 日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書簿、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

ACTIVE MATRIX TYPE DISPLAY

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を \_\_\_\_\_ とし、  
（該当する場合） \_\_\_\_\_ に訂正されました。

☐ was filed on \_\_\_\_\_  
as United States Application Number or  
PCT International Application Number  
\_\_\_\_\_ and was amended on  
\_\_\_\_\_ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について虚偽な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

# Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づき国際出願、又は外国での特許出願もしくは発明考証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明考証の外国出願を以下に、枠内をマークすることで、示しています。

## Prior Foreign Application(s)

外国での先行出願

11-142627

(Number)  
(番号)

Japan

(Country)  
(国名)

May 24, 1999

(Day/Month/Year Filed)  
(出願年月日)

## Priority Not Claimed

優先権主張なし

(Number)  
(番号)

(Country)  
(国名)

(Day/Month/Year Filed)  
(出願年月日)

私は、第35編米国法典119条(e)項に基いて下記の米特許出願規定に記載された権利をここに主張いたします。

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

私は、下記の米国法典第35編120条に基いて下記の米特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各種求願範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米特許出願に開示されていない限り、その先行米特許出願提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

(Status: Patented, Pending, Abandoned)  
(現況: 特許許可済、係属中、放棄済)

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

(Status: Patented, Pending, Abandoned)  
(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づき表明が全て真実であると信じていること、さらに故意にされた虚偽の表明及びそれと同等の行為は米国法典第18編1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 366(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 366(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.86 which became available between the filing date of the prior application and the national or PCT International filing date of application.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

# Japanese Language Declaration

(日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁理士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Attorney	Reg. No.
Patrick G. Burns	29,367
Roger D. Greer	26,174
Lawrence J. Crain	31,497
Steven P. Fallon	35,132

Attorney	Reg. No.
James K. Folker	37,538
Jonathan D. Feuchtwang	41,017
B. Joe Kim	41,895
Joel H. Bootzin	42,343

直接電話連絡先: (名前及び電話番号)

Send Correspondence to:  
 Direct Telephone Calls to: (name and telephone number)  
 Patrick G. Burns, Esq.  
 Greer, Burns & Crain, Ltd.  
 Sears Tower - Suite 8660  
 Chicago, IL 60606 (312) 993-0080

唯一または第一発明者名

Full name of sole or first inventor  
 Yoshio NAGAHIRO

発明者の署名

日付

Inventor's signature

Date

住所

Residence

国籍

Citizenship  
 Japan

私書箱

Post Office Address c/o FUJITSU LIMITED,  
 1-1, Kamikodanaka 4-chome, Nakahara-ku,  
 Kawasaki-shi, Kanagawa 211-8588 Japan

第二共同発明者

Full name of second joint inventor, if any

第二共同発明者

日付

Second inventor's signature

Date

住所

Residence

国籍

Citizenship

私書箱

Post Office Address

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)